







Technical Data

Item Description	Available Materials	Typical Dimensions	Sample Profile
Foster-Wheeler Hat Channel	Aluminized Steel Galvanized Steel	Thicknesses: 16, 18 Gauge Flange Width: 7/8" Depth: 1/2" Perforated Crown Width: 1-7/8" Lengths: 10'	
H-Bar	Aluminized Steel Stainless Steel	Thicknesses: 18, 16, 14 Gauge Flange Heights: 6" Depth: Varies per Insulation Thickness	
Modified H-Bar, with Shop-Applied Weld Pin	Aluminized Steel Stainless Steel	Thicknesses: 18, 16, 14 Gauge Rear Flange Height: 2" Front Flange Height: 1-1/2" Depth Varies per Insulation Thickness	
J-Bar	Aluminized Steel Stainless Steel	Thicknesses: 1/8" Legs: 1-1/2" x 1-1/2", 2" x 2", Lengths: 10', 20', & CTL	
Angle	Hot Rolled Steel	Thicknesses: 3/16", 1/4" Widths: 1-1/2", 2", 3" Lengths: 12', 20', & CTL	
Flat Strap	Aluminized Steel Galvanized Steel Stainless Steel	Thicknesses: 3/16", 1/4" Widths: 1-1/2", 2", 3" Lengths: 12', 20', & CTL	

Note: The above illustrations and descriptions provide "sample" data and profiles. Intended use determines specific

Corporate Headquarters

290 Fortner Rd. / McEwen, TN 37101

Phone: (931) 582-6871 Fax: (931) 582-6092